

Product information

MoS2 Low-Friction 15W-40

PI 19/03/02/2017



Description

All-season, state-of-the-art motor oil manufactured from selected base oils. The high additive content which includes the solid lubricant molybdenum disulphide (MoS2) ensures optimum lubrication under extreme operating conditions and with long periods between oil changes.

Properties

- suitable for gasoline and diesel engines with and without exhaust-gas turbocharging
- outstanding emergency-running properties
- rapid oil delivery at low temperatures
- high wear resistance
- good cold-start behavior
- tested for catalytic converters
- stable to ageing and stable viscosity
- outstanding engine cleanliness

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ACEA A3 • ACEA B4 • API SL • API CF

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	100 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -25°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20°C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	150 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-40-A-93
Flash point	228 °C DIN ISO 2592
Total base number	9,0 mg KOH/g DIN ISO 3771



Technical data

Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color / appearance	grau

Areas of application

Motor oil for gasoline, diesel and turbocharged engines. Especially suitable where there are long intervals between oil changes and extreme operating conditions.

Application

The operating materials instructions of the motor vehicle and engine manufacturer must be followed.

Available pack sizes

1 l Canister plastic	2570 BOOKLET
1 l Canister plastic	1932 D-RUS-UA
4 l Canister plastic	2631 BOOKLET
4 l Canister plastic	1949 D-RUS-UA
5 l Canister plastic	2571 BOOKLET
5 l Canister plastic	1933 D-RUS-UA
20 l Canister plastic	2572 D-GB-I-E-P
60 l Drum sheet metal	2573 D-GB
205 l Drum sheet metal	2574 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.