

# Product information

## Brake Anti-Squeal Paste

PI 21/12/01/2018



### Description

Brake Anti-Squeal Paste has been specially developed from synthetic and ceramic materials which eliminate brake squeals arising between the brake piston or contact surface and the brake lining.

### Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

### Technical data

Form	pastös, flüssig / pastelike, liquid
Color / appearance	blau / blue
Base	synthetische u. keramische Wirkstoffe
Density	1,08 g/ml
Operating temperature range	-40 bis +200 kurzfristig bis +250 / -40 to +200 short term +250 °C als Schmierpaste / as lubricating agent  -40 bis +1200 / -40 to +1200 °C als Trennpaste / as release agent
Flash point	>210 °C
Odor	schwach / slightly
Shelf life in original sealed container	36 months

### Areas of application

Brake Anti-Squeal Paste has been specially developed for the assembly, repair and maintenance of brake systems. Used for basic lubrication and as a preventive measure against brake squeals. However, it is also universally suitable for numerous applications apart from brake systems.

### Application

With floating brake callipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After the solvent has evaporated, coat cleaned parts with Brake



Anti-Squeal Paste on all sliding surfaces, channels and contact surfaces.

### Comment

Do not under any circumstances allow Brake Anti-Squeal Paste to get onto the friction surface of the brake lining or the brake disc.

### Available pack sizes

10 g Cushion plastic	3078 D
10 g Cushion plastic	7585 RUS-UA
100 g Tube plastic	3077 D-GB-I-E-P
1 kg Can sheet metal	3084 D-GB-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**