

## Gear Oil (GL5) 75W-80



### Description

GL5 SAE 75W-80 Gear Oil is a high-performance high-pressure gear oil based on synthetic and mineral base oils and high-quality additives. Enables smooth and precise shifting action even in low temperatures. Can also be used to deal with unwanted noise and to solve gear-changing problems.

### Properties

- excellent viscosity/temperature properties
- for eliminating shifting problems
- outstanding resistance to oxidation
- outstanding friction characteristics
- outstanding corrosion protection
- very good low-temperature properties
- excellent wear resistance
- optimum stability to aging

### Specifications and approvals:

API GL5 • MIL-L 2105 C

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Peugeot Citroen (PSA) B71 2330

### Technical data

SAE class (gear oils)	75W-80 SAE J306
Density at 15 °C	0,875 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	52,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	135 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color number (ASTM)	L2,5 DIN ISO 2049

### Areas of application

Specially developed for use in Peugeot and Citroen manual transmissions. Can also be used in other manual transmissions to deal with unwanted noise and to solve gear-changing problems. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

### Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Can plastic	3658 D-GB-I-E-P
1 l Can plastic	7619 D-RUS-UA
1 l Can plastic	20463 D-PL-H-RO-TR
20 l Canister plastic	3690 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**