

2-Cycle Power Saw Oil

Description

Two-Stroke Motor Saw Oil is a high-quality, high-performance engine oil which has been specially developed for the lubrication of air-cooled, high-performance, two-stroke engines in motor saws. This oil exceeds the stringent requirements for engine oils which have been set by the leading motor saw manufacturers. Selected base oils in association with the latest additive technology provide for optimum lubrication and prevent wear and the build-up of deposits even under extreme operating conditions. Can be used in all makes of high-performance motor saws with and without catalytic converter. Specifications / Approvals: API TC

Properties

- prevents the build-up of deposits
- minimizes wear
- optimum lubrication under all operating conditions

Specifications and approvals:

API TC

Technical data

Density at 15 °C	0,880 g/cm ³ DIN 51757
Viscosity at 40 °C	73,1 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,85 mm ² /s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Flash point	156 °C DIN ISO 2592
Pour point	-24 °C DIN ISO 3016
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	rot

Areas of application

Zur Schmierung von 2-Takt Hochleistungsmotorsägen mit- und ohne Katalysator.

Application

Use as normal for two-stroke motor saws. The motor manufacturer's instructions must be followed.



Available pack sizes

1 l Canister plastic	1282 D
1 l Canister plastic	8035 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.